


Marinelite®

10" COLOR LCD Fish Finder


MODEL FP1021S



- High contrast and brightness adjusting effect, suitable for use in bright light and at night;
- Advanced DSP high image supersonic digital processing technology, realizing the low blind spot and the high resolution echo;
- Full quick sampling, let every fish be shown;
- Dual frequency display, and multiple modes of background with human design;
- Stable performance, comparable with foreign brand products;
- Professional design, beautiful and fashionable, delicate and durable, containing multi-language menu display function.

Optional Transducers

A-TD372B



1.2Kw

A-TD32B



1.8Kw

A-TD38R



1Kw

A-TD382R



1.8Kw

A-TD68R



2Kw

A-TD882R



3Kw

SPECIFICATIONS

GENERAL

TX Frequency	50&200KHz Dual frequency
Output Power	1000 ~ 1500W
Accuracy	± 1%
Sensitivity	-95dBm
Alarm	Depth , Voltage, Temperature
Language	Chinese, English, Traditional

INTERFACE

Input data	IEC61162-1(NMEA0183)RMC、GLL
Output data	IEC61162-1(NMEA0183)DPT、DBT(After GLL and RMC Input)
Serial port to print	Suitable for printer DPU-414

POWER SUPPLY

DC 24V (11 ~ 35V)

ENVIRONMENTAL CONDITION


Ambient Temperature	-10 °C ~ +40 °C	Compliance with IEC60945 standard
Relative Humidity	10 ~ 90%	

DISPLAY UNIT

Display Unit	Dual frequency,Zoom
Expansion Mode	Auto Expansion, Manual Zoom, Bottom Lock
Sweep Speed	7steps(stop, 1/8, 1/4, 1/2, 1/1, 2/1, 3/1)
Display color	Echo color: 5 color Background color: black, blue


→ **Note:** Specifications are subject to change without notice.

INTERCONNECTION DIAGRAM




DIMENSIONS

Flush mount



Bracket mount



Marinelite® NANTONG SAIYANG ELECTRONICS CO.,LTD.



TEL: (+86)0513-89129287/89129288
EMAIL: Saiyang@ova.com.cn
<https://www.saiyangmarine.com>
South Floor 4/5, Building 3, , Building 3, Maipu Technology Park, Xinsheng Road, Chongchuan District, Nantong City, Jiangsu Province