



FEATURES

- **Industry Grade GPS Antenna**
- **Rugged Weatherproof plastic housing**
- **Provides Positional Data in AIS Transmissions**
- **Fully waterproof (IP67)**
- **Low noise integrated amplifier**
- **Voltage: 2.5 – 5.5 V dc**
- **Storage temperature: -40°C to +100°C**
- **High performance GPS patch antenna**

ANTENNAS & AERIALS

AG100 GPS ANTENNA

SKU: COM-0018

OVERVIEW

The AG100 is a GPS antenna for use with the T200B Class B AIS Transceiver and all Comar AIS receivers with a GPS input. A high performance GPS patch antenna and a low noise amplifier are integrated into a fully waterproof enclosure, providing excellent antenna signal amplification and out-band filtering with rejection. Supplied with external flagpole-style mount for cabin-roof mounting.

APPLICATIONS

- For providing Positional Data in AIS Transmissions
- Improving Safety at Sea

RELATED PRODUCTS

AV400 - Commercial Antenna for AIS

AV300 - Fibreglass VHF antenna

AV100 - Masthead Antenna, Stainless Steel Whip

Comar's range of AIS Transponders

PHYSICAL

Weight:	150 g (without cable)
Dimensions:	Antenna: Dia. 80 mm H 71.3 mm
Mounting:	1 Inch 14 TPI threaded mounted
Mounting Base:	W 110 mm L 70 mm H 75.2 mm
Construction:	Plastic, Centre-fed TNC connector for antenna output

ENVIRONMENTAL

Operating Temp:	-30 °C to +80 °C
Storage Temp:	-40 °C to +100 °C
Relative Humidity:	40% to 95% non-condensing
Water Resistance:	100% waterproof IP67

ELECTRICAL

Supply Voltage:	5.0 V dc
Current Consumption:	18 mA @ 5.0 V dc
VSWR:	1.5 max
Output Impedance:	50 Ω
Center Frequency:	1575.42 MHz
Gain:	30 +/-4.5 dB
Noise Figure:	2.0 max
Bandwidth:	2 MHz min.
Cable:	10 metre RG58 A/U
Connections:	TNC connector



Copyright © 2018 Comar Systems Ltd. - AG100 Datasheet v06r02