

COMPASS & HEADING / RATE OF TURN REPEATERS

MD77ROT120 DIAL RATE OF TURN INDICATOR

SKU: F077203

View Online ›

FEATURES

- **Clear and Easily Read Dial Display**
- **Rate of Turn up to 120°min**
- **Panel or Bulkhead Mounted**
- **Touch Controls**
- **Local and Remote Dimming Control**
- **Automatic Detection of Previously Lost Data**
- **Digital NMEA 0183**

OVERVIEW

The MD77ROT120 is a NMEA-based Rate of Turn Indicator, displaying the Rate in degrees per minute. Housed in a robust, compact aluminium enclosure with a touch panel for background and pointer illumination, the MD77ROT120 is ideal for any vessel.

The MD77ROT120 provides a clear and easy to read 118 mm diameter analogue display graduated in 4 degrees per minute increments. Rate range: Up to 120 degrees per minute to Port and Starboard.

Compact and rugged, the MD77ROT120 offers a solution for locations where the available space is limited and may be either bulkhead or panel mounted. Finished in Jet Black (RAL9005) Fine-texture Powder Coat to complement other marine navigation equipment.

The MD77ROT120 from Marine Data: flexible in application, easy to install and simple to maintain.

APPLICATIONS

- To display Rate of Turn (ROT) data transmitted from NMEA 0183 compatible marine equipment at a convenient location

ACCESSORIES

- Panel Mounting Kit (Supplied)
- Bulkhead Bracket Mounting Kit
- Remote Dimmer Control (0-24 V dc)

RELATED PRODUCTS

- MD68ROT - Rate of Turn Indicator (Dial Ø 164 mm)
- MD77ROT - Rate of Turn Indicator (Dial Ø 118mm)
- MD67ROT - Weatherproof Rate of Turn Indicator (Dial Ø 118 mm)

TYPE APPROVED PRODUCT
DNV
DNV.COM/AF

SPECIFICATIONS


PHYSICAL	
Weight:	1.25 kg (on bracket)
Dimensions:	H 166 mm; W 200 mm; D 87 mm (on bracket) Fascia 144 x 144 mm; dial Ø 118 mm 140 mm square panel cut out
Mounting:	Panel or Bulkhead (accessory)
Connections:	1 x data cable to 15-pin D-sub plug M4 earth stud
Construction:	Aluminium alloy enclosure
Finish:	Jet Black (RAL9005) Fine-texture Powder Coat


ELECTRICAL	
Power Supply:	24 V dc (18-32 V); 6 W
Data Input:	Digital RS422 NMEA 0183; 4800 / 9600 / 19200 / 38400 Baud, auto-selecting
Data Sentence:	ROT ($–ROT,x.x,A*hh<CR><LF>
Output:	External Alarm Loop (optional)
Cable:	Supplied with 2.5 m multi-core data cable


OPERATIONAL	
Performance:	±0.5°/min accuracy; Alignment rate in excess of 40° per second
Dial Illumination:	Backlit white
Display:	Rate of Turn, dial scale graduated in 4° per minute rate increments: full scale deflection 140°/min
LED Indicators:	Fault Indication = Red (RD); Set-up Mode = Blue (BU)
Loss of Valid Data:	Pointer assumes a vertical downward position Red FAULT LED Illuminated


ENVIRONMENTAL	
IEC 60945 Equipment Category:	Protected Area
Operating temp:	-15°C to +55°C
Storage temp:	-25°C to +70°C
RoHS:	Compliant
Compass Safe Distance:	Standard: 85cm Steering: 45cm

APPROVALS	
Conforms with:	BS EN 60945:2002 Inc. corrigendum April 2008 (BSI, 2008) BS EN 61162-1:2016 (BSI, 2016) BS EN 62288:2014 (BSI, 2016) ISO 20672:2007, IMO Resolution A.694(17) IMO Res. MSC.36(63) (IMO, 1994) IMO Res. MSC.97(73) (IMO, 2000) IMO Res. MSC191(79) (IMO, 2004)
Type Approval:	DNV - When used with a Type Approved Rate of Turn Sensor in accordance with IMO Resolution A.526 (13)









All dimensions in mm

Copyright © 2022 Marine Data Systems Ltd. - MD77ROT120 Datasheet v06r05

Vittlefields Technology Centre, Forest Road, Newport, Isle of Wight, United Kingdom. PO304LY

Marine Data Systems Ltd. reserves the right to make changes to its products and specifications without prior notice.